



Data Security



Remote Upgrade



Breakpoint Retransmission



Pre-assembled, tested

Technical Parameter

Basic Parameter	
Input Voltage	5V
Power	2W
Size (Length × Width × Tickness)	96 ± 2mm × 49 ± 2mm × 32±2mm
Operation Temperature Range	-30 ~ 60°C
Operation humidity	0 ~ 100% RH (No condensing)
Operation altitude	<4000m
Water Protection	IP65

Ethernet interface		
Port	RJ45	
Cable length	0.5m	
Waterproof level	IP65	
Commucation method	LAN & WiFi	

APP / WEB	
English	
UART:115200bps Ethernet:10 / 100M adaptive	
100m	
AP / STA / AP + STA	
802.11 b / g / n	
2.412GHz-2.484GHz	
CE / RCM	
	English UART:115200bps Ethernet:10 / 100M adaptive 100m AP / STA / AP + STA 802.11 b / g / n 2.412GHz-2.484GHz

Features

- · Wi-Fi + LAN integrated into one, for centralized deployment and management simplified configuration & O&M
- · Data encrypted to ensure data security
- $\cdot \ Supports \ breakpoint \ retransmission \ \ automatic \ disconnection \ of \ broken \ links, \ reconnection \ and \ subsequent \ transmission \ to \ prevent \ data \ loss$
- \cdot Remote upgrade inverter program update without going on-site
- · Pre-assembled, tested and shipped no on-site installation required, stable performance

